

SUPER CIRCULATION WATER PUMP



**XTRA-LARGE
PRE-STRAINER**



**HI-POWER
EFFICIENT DRIVE**



**STRONG &
ROBUST BODY**



**QUIET
OPERATION**



**RELIABLE POWER
COMPONENTS**



**SUPERIOR FLOW
& LIFT RATE**



**CONTINUOUS
NON-STOP
FUNCTION**



**ENERGY
EFFICIENT**

PPO Material Impeller & Diffuser

SIC Reliable Mechanical Sealing

Die cast Aluminium Motor Casing

IP 55 rated Protected Terminal Box
Water-proof sealed bearings
Resistant to water and humidity



Specifications:

Model No	Power			Ø Inch/mm	Max-Head (m)	Max-Flow (m3/H)	Weight Unit (Kg)
	AC Voltage	KW	HP				
RBX-150	220V	1.1	1.5	2.0/63	18	30	19
RBX-200	220V	1.5	2	2.0/63	19	35	21
RBX-300	220V 380V	2.2	3	2.0/63	20	38	23
RBX-350	220V 380V	2.6	3.5	2.0/63	21	40	24
RBX-400	380V	3	5	2.0/63	18	48	36



RBX SERIES

Specially manufactured for use in Salt/Marine water

Model No	Power			Ø Inch/mm	Max-Head (m)	Max-Flow (m3/H)	Weight Unit (Kg)
	AC Voltage	KW	HP				
RNX-1500	220V	1.1	1.5	2.0/63	18	35	23
RNX-2000	220V	1.5	2	2.0/63	18	35	24
RNX-3000	220V	2.2	3	2.0/63	20	40	25
RNX-4000	220V / 380V	3	4	2.5/75	20	43	26
RNX-5000	220V / 380V	3.8	5	2.5/75	21	50	32
RNX-5500	380V	4	5.5	2.5/75	22	60	34
RNX-7500	380V	5.5	7.5	2.5/75	22	75	37



RNX SERIES

Model No	Power			Ø Inch/mm	Max-Head (m)	Max-Flow (m3/H)	Weight Unit (Kg)
	AC Voltage	KW	HP				
RLB-4000	380V	3	4	3.0/90	19	60	37
RLB-5500	380V	4	5.5	3.0/90	20	80	40
RLB-7500	380V	5.5	7.5	3.0/90	21	95	43
RLB-10000	380V	7.5	10	3.0/90	22	110	50



RLB SERIES

Model No	Power			Ø Inch/mm	Max-Head (m)	Max-Flow (m3/H)	Weight Unit (Kg)
	AC Voltage	KW	HP				
RVF-150	220V	1.1	1.5	2.0/63	18	30	19
RVF-200	220V	1.5	2	2.0/63	19	35	21
RVF-300	220V	2.2	3	2.0/63	20	38	23



RVF SERIES
(Variable Speed)

Comparison of ReOcean PRO Circulation Pumps to other brands:

ReOcean RNX Series Specifications:

Model No	Power			Ø Inch/mm	Max-Head (m)	Max-Flow (m3/H)	Weight Unit (Kg)
	AC Voltage	KW	HP				
RNX-1500	220V	1.1	1.5	2.0/63	18	35	23
RNX-2000	220V	1.5	2	2.0/63	18	35	24
RNX-3000	220V	2.2	3	2.0/63	20	40	25
RNX-4000	220V / 380V	3	4	2.5/75	20	43	26
RNX-5000	220V /380V	3.8	5	2.5/75	21	50	32
RNX-5500	380V	4	5.5	2.5/75	22	60	34
RNX-7500	380V	5.5	7.5	2.5/75	22	75	37



RNX SERIES

Emaux E-turbo Pump Specifications:

MODEL	INPUT(kW)	Power (HP)	Max. Head (in m)	Max. Flow rate (m3/h)	Weight (in kg)
ET 075	0.75	0.75	15	19	14.5
ET 100	1.1	1	18	22	14.5
ET 150	1.5	1.5	19	26	15
ET 200	1.8	2	20	29	15.2
ET 300	2.2	3	21	32	15.7

Data obtained from Emaux website



Aqvastar QR pump Specifications:

MODEL	INPUT(kW)	Power (HP)	Max. Head (in m)	Max. Flow rate (m3/h)	Weight (in kg)
QRR050S	0.37	0.5	15	21	NA
QRR075S	0.55	0.75	16	22	NA
QRR100S	0.75	1	19	25	NA
QRR150S	1.1	1.5	22	29	NA
QRR200S	1.5	2	24	33	NA
QRR300S	2.2	3	26	36	NA

Data obtained from Aquvastar website



Supreme workhorse , Continuous- 24x7 operation, reliable/ High Powered flow and Lift rate guaranteed - Trusted, proven and used by swimming pools and oceanariums all over the world!

